



Desktop Label Printer

Simply connect to a computer to design labels and print labels.

- Plug and Print with no printer driver required (For P-touch Editor Lite version)
- Print on 3.5, 6, 9, 12, 18, 24mm TZe laminated labels
- Compatible with Windows® and Mac OS® systems





With its in-built P-touch Editor Lite software and fast print speed, labels can be created and printed whenever require. Simply plug-in, design and print with no printer driver installation required.

P-touch
PT-P700

Design and print durable labels on PC or Mac OS® systems

PT-P700 label printer helps to organise offices with clear identification labels for file folders, archived documents, USB thumbdrives, and shelves. P-touch Editor software allows the use of the computer fonts, images, logos, and frames on labels. With a wide variety of TZe laminated labels colours and sizes to choose from, professional looking labels can be generated to help organise items in the office efficiently.



Choose from any of installed true type fonts

Include frames around text

Prints from 3.5mm to 24 mm label width

30mm per second fast print speed

Add a range of installed symbols to labels

Add a logo or image to labels

Easy to connect, use and share in the office

Built-in automatic cutter

TZe laminated labels – designed to last

Brother's TZe laminated tapes consist of six layers of materials, resulting in a thin yet extremely strong label. The direct thermal transfer ink is sandwiched between two protective layers of PET (polyester film) which protect the text against the effects of liquids, abrasion, temperature, chemicals, and sunlight. As the labels are tested to the extreme, professional quality labels have been designed to last.



Abrasion
Resistant




Chemical
Resistant



Fade
Resistant



Laminated



Temperature
Resistant



Water
Resistant



Easy Peel



PT-P700

Clearly identify items with a durable TZe laminated label

Around the home, offices, schools, shops, and other places of work, there are many uses of the long lasting and durable TZe laminated labels. Common applications include:

Cables and plugs, Office equipment, File folders, Filing cabinets, Staff and visitor name badges, Signages, Mail rooms, Notice boards, Shelves, Telephone extension numbers.



Specification

General

Package content	PT-P700 Label Printer TZe-251 24mm Black on White tape, (4m long) AD-E001A AC Power adapter USB cable User guide
Language support	English, French, German, Dutch, Italian, Spanish, Portuguese, Danish, Norwegian, Swedish, Finnish*, Czech*, Hungarian*, Polish* *P-touch Editor Lite only

Features

Interface	USB 2.0 (Mini-B type connector)
Power	AD-E001A AC Power adapter (included) 6pcs of AA Alkaline batteries (LR06) (not included) 6pcs of Rechargeable batteries (HR06) (not included)
Print speed	30mm per second (AC Power adapter)
Print resolution	180dpi
Maximum print height	18.1mm
Cutter type	Automatic full cutter
Label length	25mm - 300mm (P-touch Editor Lite) 25mm - 1000mm (P-touch Editor 5.4)
Vertical text printing	Yes
Mirror printing	Yes
Copies / Sequential numbering	1 - 200 (P-touch Editor Lite) 1 - 5000 (P-touch Editor 5.4)

Supplies

Tape	TZe tape
Tape width	3.5mm, 6mm, 9mm, 12mm, 18mm, 24mm

Weight & Dimension

78 x 143 x 152mm | 710g

Label Creation

Font	Truetype fonts
Font style	Normal, Bold, Italic, Underline, Outline, Shadow, Shadow Light, Horizontal, Surround, Frame Out, Inverted, Strikethrough
Font size	up to maximum print height (approximately 72 point)
Symbol	Truetype fonts
Template	88
Image support	JPG, BMP, TIFF, PNG, GIF, DIB, WMF, EMF, ICO, screen capture function
Frame	10 (P-touch Editor Lite) 153 (P-touch Editor 5.1 and above)
Barcode	CODE 39, ITF 2/5, EAN-13, EAN-8, UPC-A, UPC-E, CODABAR, GS1-128 (UCC/EAN-128), GS1 DATABAR (RSS), GS1 COMPOSITE, ISBN-2, ISBN-5, POSTNET, LASER BARCODE, GS1 DATABAR, PDF417, QR CODE, MICRO QR CODE, DATA MATRIX, MAXICODE, AZTECCODE
Database connection support	csv, txt, mdb, xls Microsoft® SQL server database (Windows® only)

System requirements

Operating System	Microsoft® Windows Vista Microsoft® Windows 7 Microsoft® Windows 8 Mac® OS X 10.6.8/1.7.x/10.8.x
Interface	Windows® : USB Port (USB Spec. 1.1, 2.0 or 3.0 protocol) Mac® OS USB Port (USB Spec. 1.1 or 2.0 protocol)
Memory requirement	Windows® Vista: 512 MB or more Windows® 7: 1 GB (32-bit) or 2 GB (64-bit) or more Windows® 8: 1 GB (32-bit) or 2 GB (64-bit) or more Mac® OS X : 2 GB or more
Monitor	Windows® : SVGA/High Color or more Mac® OS: More than 256 colors
Microsoft® Office support for P-touch add-in	Microsoft® Word 2003, 2007, 2010 Microsoft® Excel 2003, 2007, 2010 Microsoft® Outlook® 2003, 2007, 2010

