

# BOOST YOUR PRODUCTIVITY

MFC-L2885DW

Enjoy the versatility within one machine



# GO FURTHER WITH A BUSINESS PARTNER YOU CAN RELY ON

Enjoy top-class print speeds, enhanced mobile connectivity and cost-saving innovations with Brother's range of monochrome laser printers and Multi-Function Centres.





## Double the print, half the paper

Automatic duplex printing uses up to 50% less paper.



### Less reloads reduced waste

Lower your usage by optimising the resolution for less toner reloads — thus cutting down the amount of plastics used.

[- 	Ξ	- ] _))

brother

#### Quiet as a whisper

Reduce noise and energy consumption with Quiet Mode.

_	_
	1/2
	V
٩	<b>_</b>

## A more efficient use of resources

Maximise every sheet of paper with N-in-1 printing giving you up to 4 pages per side.

#### Productivity that keeps going



#### High print speed

Get your work out efficiently with up to 34ppm, fast warm-up and first page-out of less than 8.5s \*Some features available on selected models only.



#### Tailored to what you need

Choose from our range of printers that caters to your business needs. Plus, streamline your workflows with convenient features such as Mobile Printing, Wi-Fi Direct and NFC.

# WEARE #

A4 Laser MFP (Multi-Function Printer) and Printer (Mono +30ppm)

## 5 Consecutive Years

(from 2018 to 2022)

\*IDC Quarterly Hardcopy Peripherals Tracker, 2023 Q2

brother

## **Streamlined connectivity**

Streamline your workflows with the Brother Mobile Connect app. Print, scan and copy even on the go\*, through added integration with apps on Android and Apple devices.

Plus, enjoy cross-platform compatibility to various cloud services including OneDrive, Google Drive, SharePoint and OneNote.



Weight	11.4kg	10.1kg	11.6kg	11.8kg
Dimension (W X D x H)	410 ×399 ×319 mm	410 ×399 ×272 mm	410 ×399 ×319 mm	410 ×399 ×319 mm
Dimension and Weight		15,000	pages	
Drum			2560	
High-Yield Toner <sup>ii</sup>		1,200 TN25 2,000	60XL	
Supplies Standard-Yield Toner <sup>ii</sup>			1560 pages	
Printing with Quiet mode)	LpAm = 49 dB(A)/44 dB(A)	LpAm = 49 dB(A)/44 dB(A)	LpAm = 49 dB(A)/44 dB(A)	LpAm = 49 dB(A)/44 dB(A)
Power Source Noise Level (Printing/	AC 50/60Hz	AC 50/60Hz	AC 50/60Hz (TWN: 110-120V AC 50/60 Hz)	AC 50/60Hz (TWN: 110-120V AC 50/60 Hz)
(Printing/Printing with Quiet mode)	Approx. 470W/270W 220-240V	Approx. 470W/270W 220-240V	Approx. 470W/260W 220-240V	Approx. 470W/260W 220-240V
Power Consumption		Network Security		
	BRAdmin Pro4: Windows (by Download) Network Security	BRAdmin Pro4: Windows (by Download)	BRAdmin Pro4: Windows (by Download) Setting Lock, Network Security	BRAdmin Pro4: Windows (by Download) Setting Lock, Secure Function Lock, Network Securit
OS Combability Utilities & Solutions	only), Server 2022 (Network only) Linux: CUPS, LPD/LPRng (x86/x64 environment) BRAdmin Light: Windows (by Download);	only), Server 2022 (Network only) Linux: CUPS, LPD/LPRng (x86/x64 environment) BRAdmin Light: Windows (by Download);	only), Server 2022 (Network only) Linux: CUPS, LPD/LPRng (x86/x64 environment) BRAdmin Light: Windows (by Download);	only), Server 2022 (Network only) Linux: CUPS, LPD/LPRng (x86/x64 environment) BRAdmin Light: Windows (by Download);
	Vindows 10, 11, Server 2012 (Network only), Server 2012 R2 (Network only), Server 2012 R2 (Network only), Server 2016 (Network only), Server 2019 (Network	2.1 The outside Windows 10, 11, Server 2012 (Network only), Server 2012 R2 (Network only), Server 2016 (Network only), Server 2019 (Network	Others:2 Lines LOD (16 characters) Others:2 Lines LOD (16 characters) Windows 10, 11, Server 2012 (Network only), Server 2012 R2 (Network only), Server 2019 (Network Server 2016 (Network only), Server 2019 (Network	Windows 10, 11, Server 2012 (Network only), Server 2012 R2 (Network only), Server 2016 (Network only), Server 2019 (Network
Emulation Display	PCL6, BR-Script3, PDF Version 1.7 KOR/TWN: 2 Lines LCD (10 characters)/ 2 Lines LCD (20 characters)	PCL6, BR-Script3, PDF Version 1.7 2.7" TFT ColorLCD	PCL6, BR-Script3, PDF Version 1.7 KOR/TWN: 2 Lines LCD (10 characters)/ 2 Lines LCD (20 characters)	PCL6, BR-Script3, PDF Version 1.7 2.7" TFT ColorLCD
Memory	256MB	256MB	256MB	256MB
Others Processor Speed	("Legal, Folio is not available for TWN/KOR) 600MHz	(*Legal, Folio is not available for TWN/KÕR) 600MHz	(*Legal, Folio is not available for TWN/KOR) 600MHz	(*Legal, Folio is not available for TWN/KOR) 600MHz
(Standard Tray) Media Size (Standard Tray)	(16 to 43lb) A4, Letter, B5 (JIS), B5 (ISO), A5, A5 (Long Edge), B6 (JIS), A6, Executive, Legal*, A4 Short, Folio*, Mexico Legal*, India Legal*	(16 to 43lb) A4, Letter, B5 (JIS), B5 (ISO), A5, A5 (Long Edge), B6 (JIS), A6, Executive, Legal*, A4 Short, Folio*, Mexico Legal*, India Legal*	(16 to 43lb) A4, Letter, B5 (JIS), B5 (ISO), A5, A5 (Long Edge), B6 (JIS), A6, Executive, Legal*, A4 Short, Folio*, Mexico Legal*, India Legal*	(16 to 43lb) A4, Letter, B5 (JIS), B5 (ISO), A5, A5 (Long Edge), B (JIS), A6, Executive, Legal*, A4 Short, Folio*, Mexico Legal*, India Legal*
Feeder (ADF) Media Weights	60 to 163g/m <sup>2</sup>	60 to 163g/m <sup>2</sup>	60 to 163g/m <sup>2</sup>	60 to 163g/m <sup>2</sup>
Automatic Document	50 sheets	NA	50 sheets	50 sheets
Manual Slot Output Tray (Face Down)	1 Sheet 120 Sheets	1 Sheet 120 Sheets	1 Sheet 120 Sheets	1 Sheet 120 Sheets
Paper Handling Input Tray (Standard)	250 sheets	250 sheets	250 sheets	250 sheets
Mobile Solutions , Brother's Cloud Apps, WebConnect Paper Handling	AirPrint, Mopria, Mobile Connect	AirPrint, Mopria, Mobile Connect	AirPrint, Mopria, Mobile Connect	AirPrint, Mopria, Mobile Connect
Near-Field Connectivity (NFC)	NA	NA	NA	Yes (Card Reader/NFC Shortcut)
Interface	Hi-Speed 2.0, Ethernet (10 Base-T/100 Base-TX), Wi-Fi Direct, Wireless Lan (2.4GHz/5.0GHz)	Hi-Speed 2.0, Ethernet (10 Base-T/100 Base-TX), Wi-Fi Direct, Wireless Lan (2.4GHz/5.0GHz)	Hi-Speed 2.0, Ethernet (10 Base-T/100 Base-TX), Wi-Fi Direct, Wireless Lan (2.4GHz/5.0GHz)	Hi-Speed 2.0, Ethernet (10 Base-T/100 Base-TX), Wi-Fi Direct, Wireless Lan (2.4GHz/5.0GHz)
PC Faxing Connectivity/Networking	NA	NA	(LPR/CUPS PC-FAX Send Driver)	Sending (Windows Uniy) (LPR/CUPS PC-FAX Send Driver)
Broadcasting	NA	NA	260 locations Receiving (Windows only)	250 locations Receiving (Windows only)
Speed Dial Group Dial	NA NA	NA NA	200 locations 20 groups	200 locations 20 groups
Memory Transmission/ Out-of-paper Reception	NA	NA	Up to 400 pages (ITU-T Test Chart, Standard Resolution, JBIG)	Up to 500 pages (ITU-T Test Chart, Standard Resolution, JBIG)
Transmission Speed	NA	NA	Approx. 2.5sec. (ITU-T Test Chart, Std resolution, JBIG)	Approx. 2.5sec. (ITU-T Test Chart, Std resolution, JBIG)
Fax Functions Modem Speed	NA	NA	33,600bps (Fax)	33,600bps (Fax)
Scan To Functions	Sharepoint (Windows only), E-mail, Image, OCR, File, FTP, FTPS	Sharepoint (Windows only), E-mail, Image, OCR, File, FTP, FTPS, Https	Sharepoint (Windows only), E-mail, E-mail Server, Image, OCR, File, FTP, FTPS	Sharepoint (Windows only), E-mail, E-mail Server, Network, Image, OCR, File, FTP, FTPS Https
Resolution (Optical/Interpolated)	Max 1,200 x 1,200 dpi/ Max. 19,200 x 19,200 dpi	Max 1,200 x 1,200 dpi/ Max. 19,200 x 19,200 dpi	Max 1,200 x 1,200 dpi/ Max. 19,200 x 19,200 dpi	Max 1,200 x 1,200 dpi/ Max. 19,200 x 19,200 dpi
(Mono/Colour) <sup>i</sup> Scanner (Method)	CIS	CIS	CIS	Dual CIS
Scan Functions Scan Speed	22.5/7.5 ipm	NA	22.5/7.5 ipm	22.5/7.5 ipm
Enlargement Ratio Copy Features	Multi Copy: Sort/Stack, N in 1	Multi Copy: Sort/Stack, N in 1	Multi Copy: Sort/Stack, N in 1	Multi Copy: Sort/Stack, N in 1
Copy Resolution Reduction/	600 x 600 dpi 25% - 400% in 1% increments	600 x 600 dpi 25% - 400% in 1% increments	600 x 600 dpi 25% - 400% in 1% increments	600 x 600 dpi 25% - 400% in 1% increments
Copy Speed (A4/Letter)	Up to 34/36 cpm	Up to 34/36 cpm	Up to 34/36 cpm	Up to 34/36 cpm
2-sided Feature Copy Functions	Yes	Yes	Yes	Yes
First Print Out Time (Ready)	Less than 8.5 secs	Less than 8.5 secs	Less than 8.5 secs	Less than 8.5 secs
Print Speed (A4/Letter) Print Resolution	Up to 34/36 ppm Up to 1,200 x 1,200 dpi	Up to 34/36 ppm Up to 1,200 x 1,200 dpi	Up to 34/36 ppm Up to 1,200 x 1,200 dpi	Up to 34/36 ppm Up to 1,200 x 1,200 dpi
Key Function	DCP-L2640DW Print, Scan and Copy	DCP-L2680DW Print, Scan and Copy	MFC-L2805DW Print, Scan, Copy and Fax	MFC-L2885DW Print, Scan, Copy and Fax
	londher	brother	bother	hunther .
	bender	bother	the second secon	

<sup>i</sup> In accordance with ISO/IEC17991 <sup>ii</sup> In accordance with ISO7779 <sup>ii</sup> In accordance with ISO/IEC 19752 <sup>iv</sup> Information correct as at the time of publication and may change without prior notice.

	HL-L2460DW
Key Function	Print only
Print Speed (A4/Letter)	Up to 34/36 ppm
Print Resolution	Up to 1,200 x 1,200 dpi
First Print Out Time (Ready)	Less than 8.5 secs
2-sided Feature	Yes
Connectivity/Networking	
Interface	Hi-Speed 2.0, Ethernet (10 Base-T/100 Base-T/3), Wi-Fi Direct, Wireles Lan (2.4GHz/5.0GHz)
Mobile Solutions	AirPrint, Mopria, Mobile Connect
Paper Handling	
Input Tray (Standard)	250 sheets
Manual Feed Slot	1 Sheet
Output Tray (Face Down)	150 Sheets
Media Weights (Standard Tray)	60 to 163g/m² (16 to 43lb)
Media Size	A4, Letter, B5 (JIS), B5 (ISO), A5, A5 (Long Edge), B6 (JIS), A6, Executive, Legal*, A4 Short, Folio*, Mexico Legal*, India Legal*
(Standard Tray)	(*Legal, Folio is not available for TWN/KOR)
Others	
Processor Speed	600MHz
Processor Speed Memory	128MB
Processor Speed Memory Emulation	128MB PCL6
Processor Speed Memory	128MB PCL6 1 Line LCD (16 characters)
Processor Speed Memory Emulation	128MB PCL6 1 Line LCD (16 characters) Windows 10, 11, Server 2012, Server 2016, Server 2019, Server2022 Linux: CUPS, LPD/LPRng (x86/x64 environment)
Processor Speed Memory Emulation Display OS Combability Utilities & Solutions	128MB PCL6 1 Line LCD (16 characters) Windows 10, 11, Server 2012, Server 2016, Server 2019, Server2022 Linux: CUPS, LPD/LPRng (x86/x64 environment) BRAdmin Light: Windows (by Download); BRAdmin Pro4: Windows (by Download)
Processor Speed Memory Emulation Display OS Combability	128MB PCL6 1 Line LCD (16 characters) Windows 10, 11, Server 2012 R2, Server 2016, Server 2019, Server2022 Linux: CUPS, LPD/LPRng (x86/x64 environment) BRAdmin Light: Windows (by Download);
Processor Speed Memory Emulation Display OS Combability Utilities & Solutions	128MB PCL6 1 Line LCD (16 characters) Windows 10, 11, Server 2012, Server 2016, Server 2019, Server2022 Linux: CUPS, LPD/LPRng (x86/x64 environment) BRAdmin Light: Windows (by Download); BRAdmin Pro4: Windows (by Download)
Processor Speed Memory Emulation Display OS Combability Utilities & Solutions Security Features Power Consumption (Printing/Printing with Quiet mode)	128MB PCL6 1 Line LCD (16 characters) Windows 10, 11, Server 2012, Server 2016, Server 2019, Server2022 Linux: CUPS, LPD/LPRng (x86/x64 environment) BRAdrimi Ljöt: Windows (by Download); BRAdrimi Pro4: Windows (by Download) Setting Lock, Network Security Approx. 470W/270W 220-240V
Processor Speed Memory Emulation Display OS Combability Utilities & Solutions Security Features Power Consumption (Printing/Printing with Quiet	128MB PCL6 1 Line LCD (16 characters) Windows 10, 11, Server 2012, Server 2016, Server 2019, Server2022 Linux: CUPS, LPD/LPRng (x86/x64 environment) BRAdmin Light: Windows (by Download); BRAdmin Pro4: Windows (by Download) Setting Lock, Network Security Approx. 470W/270W 220-240V AC 50/60Hz
Processor Speed Memory Emulation Display OS Combability Utilities & Solutions Security Features Power Consumption (Printing/Printing with Quiet mode)	128MB PCL6 1 Line LCD (16 characters) Windows 10, 11, Server 2012, Server 2016, Server 2019, Server2022 Linux: CUPS, LPD/LPRng (x86/x64 environment) BRAdrimi Ljöt: Windows (by Download); BRAdrimi Pro4: Windows (by Download) Setting Lock, Network Security Approx. 470W/270W 220-240V
Processor Speed Memory Emulation Display OS Combability Utilities & Solutions Security Features Power Consumption (Printing/Printing with Quiet mode) Power Source Noise Level (Printing/ Printing with Quiet mode) <sup>i</sup>	128MB PCL6 1 Line LCD (16 characters) Windows 10, 11, Server 2012, Server 2016, Server 2019, Server2022 Linux: CUPS, LPD/LPPng (x86/x64 environment) BRAdmin Light: Windows (by Download); BRAdmin Pro4: Windows (by Download) Setting Lock, Network Security Approx. 470W/270W 220-240V AC 50/60Hz (TWN: 110-120V AC 50/60 Hz)
Processor Speed Memory Emulation Display OS Combability Utilities & Solutions Security Features Power Consumption (Printing/Printing with Quiet mode) Power Source Noise Level (Printing/	128MB PCL6 1 Line LCD (16 characters) Windows 10, 11, Server 2012, Server 2016, Server 2019, Server2022 Linux: CUPS, LPD/LPPng (x86/x64 environment) BRAdmin Light: Windows (by Download); BRAdmin Pro4: Windows (by Download) Setting Lock, Network Security Approx. 470W/270W 220-240V AC 50/60Hz (TWN: 110-120V AC 50/60 Hz)
Processor Speed Memory Emulation Display OS Combability Utilities & Solutions Security Features Power Consumption (Printing/Printing with Quiet mode) Power Source Noise Level (Printing/ Printing with Quiet mode) <sup>4</sup> Supplies	128MB           PCL6           1 Line LCD (16 characters)           Windows 10, 11, Server 2012, Server 2016, Server 2019, Server2022           Linux: CUPS, LPD/LPRng           (X88/x64 environment)           BRAdmin Light: Windows (by Download);           BRAdmin Pro4: Windows (by Download)           Setting Lock, Network Security           220-240V           Approx. 470W/270W           220-240V           LpAm = 49 dB(A)/44 dB(A)           TN2560
Processor Speed Memory Emulation Display OS Combability Utilities & Solutions Security Features Power Consumption (Printing/Printing with Quiet mode) Power Source Noise Level (Printing/ Printing with Quiet mode) <sup>il</sup> Supplies Standard-Yield Toner <sup>ii</sup>	128MB           PCL6           1 Line LCD (16 characters)           Windows 10, 11, Server 2012, Server 2016, Server 2019, Server2022           Linux: CUPS, LPD/LPRng           (x86/x64 environment)           BRAdmin Light: Windows (by Download);           BRAdmin Pro4: Windows (by Download)           Setting Lock, Network Security           Approx. 470W/270W           220-240V           AC 50/60Hz           (TWN: 110-120V AC 50/60 Hz)           LpAm = 49 dB(A)/44 dB(A)           TN2560           1,200 pages           TN2560XL
Processor Speed Memory Emulation Display OS Combability Utilities & Solutions Security Features Power Consumption (Printing/Printing with Quiet mode) Power Source Noise Level (Printing/ Printing with Quiet mode)' Supplies Standard-Yield Toner <sup>ii</sup> High-Yield Toner <sup>ii</sup>	128MB           PCL6           1 Line LCD (16 characters)           Windows 10, 11, Server 2012 R2, Server 2019, Server 2019, Server2022           Linux: CUPS, LPD/LPRng           (x86/x64 environment)           BRAdmin Light: Windows (by Download);           BRAdmin Pro4: Windows (by Download)           Setting Lock, Network Security           Approx. 470W/270W           220-240V           AC 50/60Hz           (TWN: 110-120V AC 50/60 Hz)           LpArm = 49 dB(A)/44 dB(A)           TN2560           1,200 pages           TN2560XL           3,000 pages           DR2560
Processor Speed Memory Emulation Display OS Combability Utilities & Solutions Security Features Power Consumption (Printing/Printing with Quiet mode) Power Source Noise Level (Printing/ Printing with Quiet mode)' Supplies Standard-Yield Toner <sup>#</sup> High-Yield Toner <sup>#</sup>	128MB           PCL6           1 Line LCD (16 characters)           Windows 10, 11, Server 2012 R2, Server 2019, Server 2019, Server2022           Linux: CUPS, LPD/LPRng           (x86/x64 environment)           BRAdmin Light: Windows (by Download);           BRAdmin Pro4: Windows (by Download)           Setting Lock, Network Security           Approx. 470W/270W           220-240V           AC 50/60Hz           (TWN: 110-120V AC 50/60 Hz)           LpArm = 49 dB(A)/44 dB(A)           TN2560           1,200 pages           TN2560XL           3,000 pages           DR2560
Processor Speed Memory Emulation Display OS Combability Utilities & Solutions Security Features Power Consumption (Printing/Printing with Quiet mode) Power Source Noise Level (Printing/ Printing with Quiet mode)' Supplies Standard-Yield Toner <sup>#</sup> High-Yield Toner <sup>#</sup> Drum Dimension and Weight	128MB           PCL6           1 Line LCD (16 characters)           Windows 10, 11, Server 2012, Server 2016, Server 2019, Server2022           Linux: CUPS, LPD/LPRng           (x86/xx84 environment)           BRAdmin Light: Windows (by Download);           BRAdmin Pro4. Windows (by Download)           Setting Lock, Network Security           200-240V           220-240V           220-240V           200-240V           220-240V           220-240V           220-240V           220-240V           220-240V           220-240V           AC 50/60Hz           LpArm = 49 dB(A)/44 dB(A)           TN2560           1.200 pages           TN2560L           3,000 pages           DR2560           15,000 pages

<sup>i</sup> In accordance with ISO/IEC17991 <sup>ii</sup> In accordance with ISO7779 <sup>ii</sup> In accordance with ISO/IEC 19752 <sup>iv</sup> Information correct as at the time of publication and may change without prior notice.



www.brotherearth.com



One-stop centre for free downloadable templates



Brother strongly recommends the use of genuine Brother consumable products only. Benefits include better quality print, greater yields per consumable, protection of your machine from damages and achievement of optimum performance. As a precaution, please note that your machine warranty may not cover any damages arising from the use of non-genuine consumables.

Microsoft, Windows, the Windows logo and/or other Microsoft products referenced herein are either registered trademarks of Microsoft Corporation in the U.S. and/or other countries. Brother and its logo are trademarks of Brother Industries Ltd., Japan. All specifications are subject to change without notice. All registered trademarks referenced herein are the property of their respective companies. Brother International Corporation, Japan.